

## Specification For Acetone

Sr. No	Characteristics	UOM	Test Method
1	Water Content, %, W/W	0-0.3	Eq. to ASTM D-1364
2	Specific gravity, 27°C/27°C	0.784 – 0.786	Eq. to ASTM D-1298
3	Residue on evaporn, %, W/V	0-0	Eq. to ASTM D-1353
4	Permanganate Test, Minutes	30-240	Eq. to ASTM D-1363
5	Miscibility (25 ml + 225 ml Water)	CLEAR	Eq. to ASTM D-1722
6	Distn Range, Including 56.1, °C	0-1	Eq. to ASTM D-1078
7	Colour, HU	0-10	Eq. to ASTM D-1209
8	Appearance	CLEAR	VISUAL
9	Alkalinity	0-0	Eq. to ASTM D-1614
10	Alcoholic Impurities	PASSES	Eq. to IS-170
11	Acetone Purity, % W/W	99.5-100	GC METHOD
12	Acidity As Acetic Acid, % W/V	0-0.002	Eq. to ASTM D-1613

Packing: - 160 Kgs of Intact drums

For Industrial Use Only

**Disclaimer:** The information contained herein with regards to all products specification, is based on technical data and tests which we believe to be reliable. However, we assume no responsibility for results obtained or damage, if any, incurred through the application of data given, since conditions of use are outside our control