RUBBER PROCESS OIL
WITPROL N – 523 (NAPHTHENIC)

DESCRIPTION :

Witprol N - 523 is Naphthenic type of oil & has fairly good colour stability & adequate high temperature properties. This oil is recommended for use in the manufacturer of tyres, mats, foot-wear, molded & extruded goods. This oil is having compatibility with NR, SBR, and PBR. It is very much preferred for coloured and non-staining rubber products.

PROPERTIES	UNIT	ASTM METHOD	SPECIFICATION
Appearance	Attribute	Visual	Clear Liquid
Colour (ASTM)	Number	ASTM D – 1500	Max.4.5
Viscosity @ 40°C	Cst	ASTM D – 445	23 ± 5
Density @ 30°C	Gms/cc	ASTM D – 1298	0.870 ± 0.03
Flash Point	°C	ASTM D – 92	Min.160
Aniline Point	°C	ASTM D – 611	83 ± 5
Pour Point	°C	ASTM D – 97	Max.1

STORAGE:

Under roof recommended storage temperature Max.35°C.

DISCLAIMER:

Our products are produced using best of raw materials, advanced equipments, professional workforce and precise QC inspection system which ensures quality at all levels.

Our products are supported by well qualified and experienced Oil & Rubber Technologists.

We also formulate customized & tailor made Rubber Process Oils suitable to varied applications.

WITMANS INDUSTRIES PVT LTD.

Off: 205&206, Kalpataru Plaza, Chincholi Bunder Road, Off S.V.Road, Malad (West), Mumbai 400 064, India. *Tel:* 91 - 22 – 40798623 *Fax*. : 91 - 22 – 28819314 *Email*: sales@witmansgroup.com

Website: www.witmansgroup.com